

LED MONITOR

AS19LED-3

LED Monitor

AS19LED-3

Panel Type	LED
Case Type	Plastic
Maximum Resolution	1280 (H) x 1024 (V)
MTBF	50,000 hrs
Active Display Area	376.32 x 301.056 (HxV)
Pixel Pitch	0.294 x 0.294 (HxV) mm
Bezel Thickness	Left/Right 20mm, Top 20mm, Bottom 35mm
Contrast Ratio	1000 : 1
Brightness	250 cd / m ²
Response Time	5m.sec (G to G)
Viewing Angle	170 / 160° (H/V)
Display Colours	16.7 M
Video Synchronisation	Yes
PC Compatibility	Yes
Aspect Ratio	4:3
VGA Auto Frequency Correction	Yes
Speakers	2
Sound Demodulation	Yes
Mute	Yes
Work Humidity	5% - 90%
Work Temperature	-10 - +50 °C
Volume +/- Power On/Off	Yes

IN / OUT INTERFACE

Video Interface	1 x BNC composite in, 1 x BNC composite out, 1 x VGA, 1 x HDMI
Audio	1 x Input
Termination	75 ohm
Certification	CE, FCC, ROHS
VESA	100 x 100
Stand Type	Table stand
Colour	Black
Button Position	Back side bottom
Packing Dimensions	510mm x 175mm x 525mm
Gross Weight	6.1kgs



POWER

Power Supply	12v DC 3 Amp
Power Consumption	25 Watt
Voltage:	110 - 240v AC
	50 - 60Hz
Power Interface	DC 2.1mm

OSD CONTROLS

Contrast, Brightness, Colour, Sharpness,
Colour temperature

OSD LANGUAGE

English, German, Italian, Spanish, French,
Russian, Portugese, Polish

ACCESSORIES

DC adaptor, Power cable, HDMI cable,
User Manual

